



The Activated Lite Carbon we use called CKG 48, is only provided by our long-term trustworthy partners. The feature that makes Lite carbon so effective in filtering the air, is the micro-meso pores structure, that is perfectly adapted to its use.

- + Lite carbon CKG 48
- + Light weight filters with minimum 18 months of life
- + Easy to handle and to mount

Optimum conditions of use:
Max. Temperature 80°C
Max. Humidity 70%



PRACTICAL CAPACITY



FLANGE



LENGTH



DIAMETER



WEIGHT



CARBON WEIGHT



CARBON BED



MATERIAL

	CODE	FILTER	M³/H	MM	CM	CM	KG	KG	CM	HOUSING	PRICE
	8984	LITE 150 PL *	150	100/125	25	14,5	1,2	0,7	2,5	PLASTIC	
	8979	LITE 300 PL *	300	100/125	45	14,5	1,8	1,2	2,5	PLASTIC	
	8983	LITE 425 PL *	425	100/125	60	14,5	2,2	1,6	2,5	PLASTIC	
	8623	LITE 425 S	425	150	35	20	4	1,9	2,5	STEEL	
	8687	LITE 600	600	150	47,5	20	4	2,2	3,5	STEEL	
NEW	4696	LITE 800	800	200	33	30	5	3,4	5,0	STEEL	
	8124	LITE 1000	1000	200	50	30	11	5,1	5,0	STEEL	
NEW	8797	LITE 1000	1000	250	50	30	11	5,1	5,0	STEEL	
	8134	LITE 1500	1500	200	75	30	15,5	7,6	5,0	STEEL	
	8140	LITE 1500	1500	250	75	30	15,5	7,6	5,0	STEEL	
	8612	LITE 2000	2000	200	100	30	19	10,2	5,0	STEEL	
	8169	LITE 2000	2000	250	100	30	19	10,2	5,0	STEEL	
	8233	LITE 2500	2500	250	100	35	23	12,2	5,0	STEEL	
	8981	LITE 2500	2500	315	100	35	23	12,2	5,0	STEEL	
	8793	LITE 3000	3000	315	100	40	26	14,3	5,0	STEEL	
	8170	LITE 3000	3000	355	100	40	26	14,3	5,0	STEEL	
	8171	LITE 3500	3500	355	100	45	33,5	16,3	5,0	STEEL	
	4090	LITE 3500	3500	400	100	45	33,5	16,3	5,0	STEEL	
	8172	LITE 4500	4500	400	100	50	36,5	18,5	5,0	STEEL	

* When ordering your Can-Lite Poly filter, please specify which flange you would like and it will be provided free of charge. 8624 for 100mm flange OR 8601 for 125mm flange.